Outline
Introduction
Atomic Sentences (summary)
Logical Consequence
Demonstrating Non-consequence

### The Validity and Soundness of Arguments

Torben Amtoft Kansas State University Introduction

Atomic Sentences (summary)

Logical Consequence

Demonstrating Non-consequence



# Road Map

Two main aims of book (p.2):

- 1. help you learn language of first-order logic (FOL)
- 2. help you learn notion of logical consequence

# Road Map

Two main aims of book (p.2):

- 1. help you learn language of first-order logic (FOL)
- 2. help you learn notion of logical consequence
- Chapter 1 takes the first step of (1)
- ► Chapter 2 takes the first step of (2)

### **Atomic Sentences**

```
A term t is built from constants and function symbols:
    father(father(max))

An atomic sentence is a predicate applied to some terms:
    Older(father(max), max)
```

### **Atomic Sentences**

A term *t* is built from constants and function symbols:

father(father(max))

An atomic sentence is a predicate applied to some terms:

Older(father(max), max)

	functions	predicates
result is	object	truth value
spelling is	lower case	capitalized
can be nested?	yes	no

# Example Worlds

	constants	functions		predicates	
		arity 1	arity 2	arity 1	arity 2
Arithmetic	0,1,2,	sin, cos	+,-		<
Family	max, claire	father		Pet	Older
Tarski's World	a, b,			Cube	LeftOf

- ▶ many functions and predicates with arity 2 are written infix: x + y, x < y, x = y
- functions can be added to Tarski's world (p.33, and homework exercises 1.13 & 1.14)
- ► The identity predicate "=" is relevant in all worlds!



#### Motivation

An argument is **not** two persons arguing back and forth, but one person presenting a series of statements in which one, the conclusion, is meant to be a consequence of the others, called the premises.

### Motivation

An argument is **not** two persons arguing back and forth, but one person presenting a series of statements in which one, the conclusion, is meant to be a consequence of the others, called the premises.

Premises	a is larger than b
	ъ is larger than с
Conclusion	a is larger than c

### Motivation

An argument is **not** two persons arguing back and forth, but one person presenting a series of statements in which one, the conclusion, is meant to be a consequence of the others, called the premises.

Premises	a is larger than b
	b is larger than c
Conclusion	a is larger than c

#### Fitch format

```
a is larger than bb is larger than ca is larger than c
```



Socrates is a man All men are mortal Socrates is mortal

Socrates is a man All men are mortal Socrates is mortal

This classical argument is

▶ valid: it is not possible for the conclusion to be false if the premises are true.

```
Socrates is a man true (history)

All men are mortal

Socrates is mortal
```

#### This classical argument is

- valid: it is not possible for the conclusion to be false if the premises are true.
- sound: it is valid, and its premises are true.

```
Socrates is a man true (history)
All men are mortal
Socrates is mortal
True (biology)
true (history: hemlock, 399 BC)
```

#### This classical argument is

- ▶ valid: it is not possible for the conclusion to be false if the premises are true.
- sound: it is valid, and its premises are true. (so also its conclusion is true)

Scruffy is a man
All men are mortal
Scruffy is mortal

This argument is

valid, as same structure as the previous argument

Scruffy is a man	false
All men are mortal	true
Scruffy is mortal	true

#### This argument is

- valid, as same structure as the previous argument
- unsound, since Scruffy is a cat (conclusion happens to be true)

Scruffy is a man	false
All men are mortal	true
Scruffy is mortal	true

#### This argument is

- valid, as same structure as the previous argument
- unsound, since Scruffy is a cat (conclusion happens to be true)

Red Sox win the World Series each year Red Sox will win the 2004 World Series



Scruffy is a man	false
All men are mortal	true
Scruffy is mortal	true

#### This argument is

- valid, as same structure as the previous argument
- unsound, since Scruffy is a cat (conclusion happens to be true)

```
Red Sox win the World Series each year False
Red Sox will win the 2004 World Series ?
```

This is also valid, but, alas, not sound.



## **Invalid Arguments**

Socrates is mortal
All men are mortal
Socrates is a man

This argument has a different structure than what we have seen, and is invalid.

### **Invalid Arguments**

Socrates is mortal true
All men are mortal true
Socrates is a man false

This argument has a different structure than what we have seen, and is invalid.

Counterexample: Socrates might be a dog

## **Invalid Arguments**

Socrates is mortal
All men are mortal
Socrates is a man

This argument has a different structure than what we have seen, and is invalid.

Counterexample: Socrates might be a dog

To decide whether an argument is

- valid: it is sufficient to examine the structure of the argument
- sound: we must examine history, biology, baseball, etc.

Therefore the focus of logic, and this course, is on validity of argument, rather than on soundness.



Given a purported argument, a counterexample is

- ▶ a world where the premises are true but the conclusion is false
- enough to show that the argument is invalid: the conclusion does not follow from the premises (is non sequitur).

Given a purported argument, a counterexample is

- a world where the premises are true but the conclusion is false
- enough to show that the argument is invalid: the conclusion does not follow from the premises (is non sequitur).

Mrs. Smith was stabbed in her bedroom
All doors and windows were locked
Only Mr. Smith and the butler were in the house
Mr. Smith stabbed his wife

Given a purported argument, a counterexample is

- a world where the premises are true but the conclusion is false
- enough to show that the argument is invalid: the conclusion does not follow from the premises (is non sequitur).

Mrs. Smith was stabbed in her bedroom
All doors and windows were locked
Only Mr. Smith and the butler were in the house
Mr. Smith stabbed his wife
the butler did it

Given a purported argument, a counterexample is

- a world where the premises are true but the conclusion is false
- enough to show that the argument is invalid: the conclusion does not follow from the premises (is non sequitur).

Mrs. Smith was stabbed in her bedroom

All doors and windows were locked

Only Mr. Smith and the butler were in the house

Mr. Smith stabbed his wife the butler did it

Atta was in Virginia on April 4, 2001

Atta was in Florida on April 11, 2001

Atta cannot have met with Iraqi agents in Prague on April 8, 2001



Given a purported argument, a counterexample is

- a world where the premises are true but the conclusion is false
- enough to show that the argument is invalid: the conclusion does not follow from the premises (is non sequitur).

Mrs. Smith was stabbed in her bedroom

All doors and windows were locked

Only Mr. Smith and the butler were in the house

Mr. Smith stabbed his wife the butler did it

Atta was in Virginia on April 4, 2001

Atta was in Florida on April 11, 2001

Atta cannot have met with Iraqi agents in Prague on April 8, 2001

Atta took an airplane...



In homeworks, you'll often be given an argument and asked to submit a world that serves as a counterexample.

```
LeftOf(a,b)
SameSize(b,c)
LeftOf(a,c)
```

In homeworks, you'll often be given an argument and asked to submit a world that serves as a counterexample.

```
LeftOf(a,b)
SameSize(b,c)
LeftOf(a,c)
```

Counterexample: a world with only small cubes, arranged like c a b

In homeworks, you'll often be given an argument and asked to submit a world that serves as a counterexample.

```
LeftOf(a,b)
SameSize(b,c)
LeftOf(a,c)
```

Counterexample: a world with only small cubes, arranged like

c a b

```
LeftOf(a,b)
b = c
LeftOf(a,c)
```

#### Counterexample:

In homeworks, you'll often be given an argument and asked to submit a world that serves as a counterexample.

```
LeftOf(a,b)
SameSize(b,c)
LeftOf(a,c)
```

Counterexample: a world with only small cubes, arranged like c a b

```
LeftOf(a,b)
b = c
LeftOf(a,c)
```

Counterexample: none, as argument is valid